

LINE SSL P 600


RECESSED


SURFACE


SUSPENDED


TRACK LIGHTS



WALL


OUTSIDE


SYSTEM LUMINAIRES



FINISH COLORS:



HOUSING:



MONTAGE:



DIFFUSER:



OPTICS/ROTATION:



LINE SSL P 600 3000K

dimensions (mm)	number of LED modules	value Φ (lm) per Led module			
		450/650/780 (lm) code	power of system (W)	940/1100/1250 (lm) code	power of system (W)
b					
595	2	SSLP8041-6	5,5 / 8,0 / 9,5	SSLP8055-6	11,5 / 13,5 / 15,3
1195	4	SSLP8045-6	11,0 / 16,0 / 19,0	SSLP8059-6	23,0 / 27,0 / 30,6
1495	5	SSLP8047-6	13,8 / 20,0 / 23,8	SSLP8061-6	28,8 / 33,8 / 38,3
1795	6	SSLP8049-6	16,5 / 24,0 / 28,5	SSLP8063-6	34,5 / 40,5 / 46,0

LINE SSL P 600 4000K

dimensions (mm)	number of LED modules	value Φ (lm) per Led module			
		450/650/780 (lm) code	power of system (W)	940/1100/1250 (lm) code	power of system (W)
b					
595	2	SSLP8042-6	5,5 / 8,0 / 9,5	SSLP8056-6	11,5 / 13,5 / 15,3
1195	4	SSLP8046-6	11,0 / 16,0 / 19,0	SSLP8060-6	23,0 / 27,0 / 30,6
1495	5	SSLP8048-6	13,8 / 20,0 / 23,8	SSLP8062-6	28,8 / 33,8 / 38,3
1795	6	SSLP8050-6	16,5 / 24,0 / 28,5	SSLP8064-6	34,5 / 40,5 / 46,0

LIGHT SOURCE:



POWER SUPPLY:



CONTROL:



NORMS:

